

**MATERIAL SAFETY DATA SHEET**

(Essentially similar to Form OSHA-20)

**Western Tube & Conduit**

Page 1 of 3

Revision Date: 3/4/2003

Phone Number: 310.669.2204

<p><b>Product Identification</b></p>	<p><b>Trade Name:</b> Galvanized Steel Tubing (1000 Series Alloys)  <b>Generic Name:</b> Not applicable  <b>Chemical Name:</b> Not applicable  <b>Chemical Family:</b> Not applicable  <b>Synonyms:</b> Not applicable</p>																								
<p><b>Hazardous Ingredients</b></p>	<table border="1"> <thead> <tr> <th>Ingredient</th> <th>CAS No.</th> <th>%</th> <th>Limit, Type</th> </tr> </thead> <tbody> <tr> <td>Iron</td> <td>7439-89-6</td> <td>98-99</td> <td>5 mg/m<sup>3</sup> fume</td> </tr> <tr> <td>Manganese</td> <td>7439-96-5</td> <td>0.45-0.85</td> <td>0.2 mg/m<sup>3</sup> ACGIH, TLV</td> </tr> <tr> <td>Carbon</td> <td>7440-44-0</td> <td>0.1-0.7</td> <td>10 mg/m<sup>3</sup> inhalable</td> </tr> <tr> <td>Silicon</td> <td>7440-21-3</td> <td>0.2</td> <td>10 mg/m<sup>3</sup> ACGIH, TLV</td> </tr> <tr> <td>Zinc (galv. coating)</td> <td>7440-66-6</td> <td>&lt;0.5</td> <td>5 mg/m<sup>3</sup> fume</td> </tr> </tbody> </table>	Ingredient	CAS No.	%	Limit, Type	Iron	7439-89-6	98-99	5 mg/m <sup>3</sup> fume	Manganese	7439-96-5	0.45-0.85	0.2 mg/m <sup>3</sup> ACGIH, TLV	Carbon	7440-44-0	0.1-0.7	10 mg/m <sup>3</sup> inhalable	Silicon	7440-21-3	0.2	10 mg/m <sup>3</sup> ACGIH, TLV	Zinc (galv. coating)	7440-66-6	<0.5	5 mg/m <sup>3</sup> fume
Ingredient	CAS No.	%	Limit, Type																						
Iron	7439-89-6	98-99	5 mg/m <sup>3</sup> fume																						
Manganese	7439-96-5	0.45-0.85	0.2 mg/m <sup>3</sup> ACGIH, TLV																						
Carbon	7440-44-0	0.1-0.7	10 mg/m <sup>3</sup> inhalable																						
Silicon	7440-21-3	0.2	10 mg/m <sup>3</sup> ACGIH, TLV																						
Zinc (galv. coating)	7440-66-6	<0.5	5 mg/m <sup>3</sup> fume																						
<p><b>Physical Data</b></p>	<p><b>Appearance and Odor:</b> Solid, metallic gray, odorless.</p> <table border="1"> <tbody> <tr> <td><b>Melting Point:</b> Not applicable</td> <td><b>Solubility (H<sub>2</sub>O):</b> Insoluble</td> </tr> <tr> <td><b>Boiling Point:</b> Not applicable</td> <td><b>pH:</b> Not applicable</td> </tr> <tr> <td><b>Vapor Pressure:</b> Not applicable</td> <td><b>Specific Gravity:</b> 7.85 at 4°C</td> </tr> <tr> <td><b>% Volatile (vol.):</b> Not applicable</td> <td><b>API Gravity:</b> Not applicable</td> </tr> <tr> <td><b>Vapor Density:</b> Not applicable</td> <td><b>Viscosity:</b> Not applicable</td> </tr> <tr> <td><b>Evaporation Rate:</b> Not applicable</td> <td></td> </tr> </tbody> </table>				<b>Melting Point:</b> Not applicable	<b>Solubility (H<sub>2</sub>O):</b> Insoluble	<b>Boiling Point:</b> Not applicable	<b>pH:</b> Not applicable	<b>Vapor Pressure:</b> Not applicable	<b>Specific Gravity:</b> 7.85 at 4°C	<b>% Volatile (vol.):</b> Not applicable	<b>API Gravity:</b> Not applicable	<b>Vapor Density:</b> Not applicable	<b>Viscosity:</b> Not applicable	<b>Evaporation Rate:</b> Not applicable										
<b>Melting Point:</b> Not applicable	<b>Solubility (H<sub>2</sub>O):</b> Insoluble																								
<b>Boiling Point:</b> Not applicable	<b>pH:</b> Not applicable																								
<b>Vapor Pressure:</b> Not applicable	<b>Specific Gravity:</b> 7.85 at 4°C																								
<b>% Volatile (vol.):</b> Not applicable	<b>API Gravity:</b> Not applicable																								
<b>Vapor Density:</b> Not applicable	<b>Viscosity:</b> Not applicable																								
<b>Evaporation Rate:</b> Not applicable																									
<p><b>Fire and Explosion Data; NFPA Standard 704 Ratings</b></p>	<table border="1"> <tbody> <tr> <td><b>Flash Point (TCC):</b> Not applicable</td> <td><b>NFPA Ratings:</b></td> </tr> <tr> <td><b>Lower Flam. Limit:</b> Not applicable</td> <td><b>Health</b> 0</td> </tr> <tr> <td><b>Upper Flam. Limit:</b> Not applicable</td> <td><b>Fire</b> 0</td> </tr> <tr> <td><b>Autoignition Temp.:</b> Not applicable</td> <td><b>Reactivity</b> 0</td> </tr> </tbody> </table> <p><b>Fire &amp; Explosion Hazards:</b> Not applicable for the solid product. Do not use water on molten metal.</p> <p><b>Products of Combustion:</b> Metal oxides, alloy elements, and oxides of carbon and nitrogen.</p> <p><b>Extinguishing Media:</b> Not applicable for the solid product. Use appropriate extinguishers for surrounding material.</p> <p><b>Fire Fighting Procedures:</b> Do not release runoff from fire control methods to sewers or waterways. Wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode and full protective clothing.</p>				<b>Flash Point (TCC):</b> Not applicable	<b>NFPA Ratings:</b>	<b>Lower Flam. Limit:</b> Not applicable	<b>Health</b> 0	<b>Upper Flam. Limit:</b> Not applicable	<b>Fire</b> 0	<b>Autoignition Temp.:</b> Not applicable	<b>Reactivity</b> 0													
<b>Flash Point (TCC):</b> Not applicable	<b>NFPA Ratings:</b>																								
<b>Lower Flam. Limit:</b> Not applicable	<b>Health</b> 0																								
<b>Upper Flam. Limit:</b> Not applicable	<b>Fire</b> 0																								
<b>Autoignition Temp.:</b> Not applicable	<b>Reactivity</b> 0																								
<p>Western Tube &amp; Conduit • 2001 East Dominguez Street • Long Beach • California • 90810</p>																									

<b>Health Hazard Information; Protective Equipment Recommended</b>	<p><b>General Effects of Overexposure:</b> Primary route of exposure is inhalation. Operations such as burning, welding, sawing, brazing, machining, and grinding may cause health effects if exposures exceed recommended limits as listed under <b>Hazardous Ingredients</b>.</p> <p><b>Eye Contact:</b> Excessive exposure to high concentrations of dust may cause irritation to the eyes. Particles of iron compounds may become imbedded in the eye and cause rust stains unless removed promptly. Use safety glasses or goggles as required for machining operations.</p> <p><b>Skin Contact:</b> Dust may cause irritation or sensitization of the skin, possibly leading to dermatitis. Protective gloves should be worn as required for handling operations.</p> <p><b>Inhalation:</b> Excessive inhalation to fumes of metal oxide particles can produce an acute reaction known as "metal fume fever". Symptoms consist of chills and fever, metallic taste in the mouth, dryness and irritation of the throat followed by weakness and muscle pain. Oxide fumes of manganese and copper have been associated with causing metal fume fever. Chronic inhalation of excessive concentrations of metal fumes may result in pneumoconiosis, pulmonary disorders, respiratory irritation, asthma, nosebleed, and ulceration of the nasal septum, as well as respiratory cancer.</p> <p><b>Ingestion:</b> Ingestion of dust may cause nausea or vomiting.</p>
<b>Emergency &amp; First Aid Information</b>	<p><b>Eye Contact:</b> Flush the affected eye(s) with water. If irritation develops, seek medical attention.</p> <p><b>Skin Contact:</b> Wash skin thoroughly with soap and water. If irritation or abrasion develop seek medical attention.</p> <p><b>Inhalation:</b> Move away from exposure to fumes and into fresh air. If symptoms of exposure develop, seek medical attention.</p> <p><b>Ingestion:</b> If ingested seek medical attention.</p>

<b>Chemical Reactivity Information</b>	<p><b>Stability:</b> Stable under normal conditions of storage and handling.</p> <p><b>Reactivity:</b> May react with strong acids to form hydrogen. Iron oxide dusts in contact with calcium hypochlorite evolve oxygen and may cause an explosion.</p> <p><b>Incompatibility:</b> May be incompatible with strong acids.</p> <p><b>Hazardous Reaction/Decomposition Products:</b> Burning produces oxides of iron, manganese, chromium and other alloying elements.</p> <p><b>Polymerization Hazards:</b> This material will not polymerize.</p>
<b>Storage &amp; Handling Procedures</b>	<p><b>Routine Handling &amp; Use:</b> Avoid breathing metal fumes or dust generated during machining operations. Practice good housekeeping.</p> <p><b>Non-Routine Handling &amp; Use:</b> Not applicable.</p> <p><b>Storage:</b> Store away from acids and incompatible materials.</p>
<b>Spill, Leak and Disposal Procedures</b>	<p><b>General Spill or Leak Procedures:</b> All materials should be handled and transported off-site in accordance with federal, state, and local regulations.</p>
<b>Regulatory Information</b>	<p><b>SARA Section 313 Notification:</b> Contains no listed substances present above the de minimis concentrations listed in 40 CFR 372 (2002). Please contact Western Tube &amp; Conduit for an update prior to completing any EPCRA report.</p> <p><b>VOC Content, Material:</b> 0</p> <p><b>VOC Content, Less Water:</b> 0</p> <p><b>Clean Air Act Ozone Depleter:</b> None listed</p> <p><b>DOT Proper Shipping Name:</b> Not regulated</p> <p><b>DOT Hazard Class:</b> None</p> <p><b>40 CFR 355 Reportable Quantity:</b> None listed</p> <p><b>49 CFR 171 Reportable Quantity:</b> None listed</p> <p><b>California Proposition 65:</b> <b><u>WARNING: This product contains chemicals known by the State of California to cause cancer, birth defects, or other reproductive harm.</u></b></p>
<p>Western Tube &amp; Conduit • 2001 East Dominguez Street • Long Beach • California • 90810</p>	

**MATERIAL SAFETY DATA SHEET**

(Essentially similar to Form OSHA-20)

**Western Tube & Conduit**

Page 1 of 3

Revision Date: 3/4/2003

Phone Number: 310.669.2204

<p><b>Product Identification</b></p>	<p><b>Trade Name:</b> Steel Tubing (1000 Series Alloys)  <b>Generic Name:</b> Not applicable  <b>Chemical Name:</b> Not applicable  <b>Chemical Family:</b> Not applicable  <b>Synonyms:</b> Not applicable</p>																											
<p><b>Hazardous Ingredients</b></p>	<table border="1"> <thead> <tr> <th data-bbox="483 499 751 531">Ingredient</th> <th data-bbox="760 499 930 531">CAS No.</th> <th data-bbox="938 499 1109 531">%</th> <th data-bbox="1117 499 1417 531">Limit, Type</th> </tr> </thead> <tbody> <tr> <td data-bbox="483 573 540 604">Iron</td> <td data-bbox="760 573 898 604">7439-89-6</td> <td data-bbox="938 573 1011 604">98-99</td> <td data-bbox="1117 573 1304 604">5 mg/m<sup>3</sup> fume</td> </tr> <tr> <td data-bbox="483 615 638 646">Manganese</td> <td data-bbox="760 615 898 646">7439-96-5</td> <td data-bbox="938 615 1060 646">0.45-0.85</td> <td data-bbox="1117 615 1417 646">0.2 mg/m<sup>3</sup> ACGIH, TLV</td> </tr> <tr> <td data-bbox="483 657 573 688">Carbon</td> <td data-bbox="760 657 898 688">7440-44-0</td> <td data-bbox="938 657 1027 688">0.1-0.7</td> <td data-bbox="1117 657 1369 688">10 mg/m<sup>3</sup> inhalable</td> </tr> <tr> <td data-bbox="483 699 573 730">Silicon</td> <td data-bbox="760 699 898 730">7440-21-3</td> <td data-bbox="938 699 979 730">0.2</td> <td data-bbox="1117 699 1417 730">10 mg/m<sup>3</sup> ACGIH, TLV</td> </tr> </tbody> </table>				Ingredient	CAS No.	%	Limit, Type	Iron	7439-89-6	98-99	5 mg/m <sup>3</sup> fume	Manganese	7439-96-5	0.45-0.85	0.2 mg/m <sup>3</sup> ACGIH, TLV	Carbon	7440-44-0	0.1-0.7	10 mg/m <sup>3</sup> inhalable	Silicon	7440-21-3	0.2	10 mg/m <sup>3</sup> ACGIH, TLV				
Ingredient	CAS No.	%	Limit, Type																									
Iron	7439-89-6	98-99	5 mg/m <sup>3</sup> fume																									
Manganese	7439-96-5	0.45-0.85	0.2 mg/m <sup>3</sup> ACGIH, TLV																									
Carbon	7440-44-0	0.1-0.7	10 mg/m <sup>3</sup> inhalable																									
Silicon	7440-21-3	0.2	10 mg/m <sup>3</sup> ACGIH, TLV																									
<p><b>Physical Data</b></p>	<p><b>Appearance and Odor:</b> Solid, metallic gray, odorless.</p>			<table border="1"> <tr> <td data-bbox="483 877 751 909"><b>Melting Point:</b></td> <td data-bbox="760 877 963 909">Not applicable</td> <td data-bbox="979 877 1417 909"><b>Solubility (H<sub>2</sub>O):</b></td> <td data-bbox="1222 877 1417 909">Insoluble</td> </tr> <tr> <td data-bbox="483 919 751 951"><b>Boiling Point:</b></td> <td data-bbox="760 919 963 951">Not applicable</td> <td data-bbox="979 919 1417 951"><b>pH:</b></td> <td data-bbox="1222 919 1417 951">Not applicable</td> </tr> <tr> <td data-bbox="483 961 751 993"><b>Vapor Pressure:</b></td> <td data-bbox="760 961 963 993">Not applicable</td> <td data-bbox="979 961 1417 993"><b>Specific Gravity:</b></td> <td data-bbox="1222 961 1417 993">7.85 at 4°C</td> </tr> <tr> <td data-bbox="483 1003 751 1035"><b>% Volatile (vol.):</b></td> <td data-bbox="760 1003 963 1035">Not applicable</td> <td data-bbox="979 1003 1417 1035"><b>API Gravity:</b></td> <td data-bbox="1222 1003 1417 1035">Not applicable</td> </tr> <tr> <td data-bbox="483 1045 751 1077"><b>Vapor Density:</b></td> <td data-bbox="760 1045 963 1077">Not applicable</td> <td data-bbox="979 1045 1417 1077"><b>Viscosity:</b></td> <td data-bbox="1222 1045 1417 1077">Not applicable</td> </tr> <tr> <td data-bbox="483 1087 751 1119"><b>Evaporation Rate:</b></td> <td data-bbox="760 1087 963 1119">Not applicable</td> <td colspan="2"></td> </tr> </table>	<b>Melting Point:</b>	Not applicable	<b>Solubility (H<sub>2</sub>O):</b>	Insoluble	<b>Boiling Point:</b>	Not applicable	<b>pH:</b>	Not applicable	<b>Vapor Pressure:</b>	Not applicable	<b>Specific Gravity:</b>	7.85 at 4°C	<b>% Volatile (vol.):</b>	Not applicable	<b>API Gravity:</b>	Not applicable	<b>Vapor Density:</b>	Not applicable	<b>Viscosity:</b>	Not applicable	<b>Evaporation Rate:</b>	Not applicable		
<b>Melting Point:</b>	Not applicable	<b>Solubility (H<sub>2</sub>O):</b>	Insoluble																									
<b>Boiling Point:</b>	Not applicable	<b>pH:</b>	Not applicable																									
<b>Vapor Pressure:</b>	Not applicable	<b>Specific Gravity:</b>	7.85 at 4°C																									
<b>% Volatile (vol.):</b>	Not applicable	<b>API Gravity:</b>	Not applicable																									
<b>Vapor Density:</b>	Not applicable	<b>Viscosity:</b>	Not applicable																									
<b>Evaporation Rate:</b>	Not applicable																											
<p><b>Fire and Explosion Data; NFPA Standard 704 Ratings</b></p>	<p><b>Flash Point (TCC):</b> Not applicable  <b>Lower Flam. Limit:</b> Not applicable  <b>Upper Flam. Limit:</b> Not applicable  <b>Autoignition Temp.:</b> Not applicable</p>		<p><b>NFPA Ratings:</b></p> <table border="1"> <tr> <td data-bbox="987 1203 1109 1234"><b>Health</b></td> <td data-bbox="1247 1203 1271 1234">0</td> </tr> <tr> <td data-bbox="987 1245 1109 1276"><b>Fire</b></td> <td data-bbox="1247 1245 1271 1276">0</td> </tr> <tr> <td data-bbox="987 1287 1109 1318"><b>Reactivity</b></td> <td data-bbox="1247 1287 1271 1318">0</td> </tr> </table>		<b>Health</b>	0	<b>Fire</b>	0	<b>Reactivity</b>	0																		
<b>Health</b>	0																											
<b>Fire</b>	0																											
<b>Reactivity</b>	0																											
<p><b>Fire &amp; Explosion Hazards:</b> Not applicable for the solid product. Do not use water on molten metal.</p> <p><b>Products of Combustion:</b> Metal oxides, alloy elements, and oxides of carbon and nitrogen.</p> <p><b>Extinguishing Media:</b> Not applicable for the solid product. Use appropriate extinguishers for surrounding material.</p> <p><b>Fire Fighting Procedures:</b> Do not release runoff from fire control methods to sewers or waterways. Wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode and full protective clothing.</p>																												
<p>Western Tube &amp; Conduit • 2001 East Dominguez Street • Long Beach • California • 90810</p>																												

<b>Health Hazard Information; Protective Equipment Recommended</b>	<p><b>General Effects of Overexposure:</b> Primary route of exposure is inhalation. Operations such as burning, welding, sawing, brazing, machining, and grinding may cause health effects if exposures exceed recommended limits as listed under <b>Hazardous Ingredients</b>.</p> <p><b>Eye Contact:</b> Excessive exposure to high concentrations of dust may cause irritation to the eyes. Particles of iron compounds may become imbedded in the eye and cause rust stains unless removed promptly. Use safety glasses or goggles as required for machining operations.</p> <p><b>Skin Contact:</b> Dust may cause irritation or sensitization of the skin, possibly leading to dermatitis. Protective gloves should be worn as required for handling operations.</p> <p><b>Inhalation:</b> Excessive inhalation to fumes of metal oxide particles can produce an acute reaction known as "metal fume fever". Symptoms consist of chills and fever, metallic taste in the mouth, dryness and irritation of the throat followed by weakness and muscle pain. Oxide fumes of manganese and copper have been associated with causing metal fume fever. Chronic inhalation of excessive concentrations of metal fumes may result in pneumoconiosis, pulmonary disorders, respiratory irritation, asthma, nosebleed, and ulceration of the nasal septum, as well as respiratory cancer.</p> <p><b>Ingestion:</b> Ingestion of dust may cause nausea or vomiting.</p>
<b>Emergency &amp; First Aid Information</b>	<p><b>Eye Contact:</b> Flush the affected eye(s) with water. If irritation develops, seek medical attention.</p> <p><b>Skin Contact:</b> Wash skin thoroughly with soap and water. If irritation or abrasion develop seek medical attention.</p> <p><b>Inhalation:</b> Move away from exposure to fumes and into fresh air. If symptoms of exposure develop, seek medical attention.</p> <p><b>Ingestion:</b> If ingested seek medical attention.</p>

<p><b>Chemical Reactivity Information</b></p>	<p><b>Stability:</b> Stable under normal conditions of storage and handling.</p> <p><b>Reactivity:</b> May react with strong acids to form hydrogen. Iron oxide dusts in contact with calcium hypochlorite evolve oxygen and may cause an explosion.</p> <p><b>Incompatibility:</b> May be incompatible with strong acids.</p> <p><b>Hazardous Reaction/Decomposition Products:</b> Burning produces oxides of iron, manganese, chromium and other alloying elements.</p> <p><b>Polymerization Hazards:</b> This material will not polymerize.</p>
<p><b>Storage &amp; Handling Procedures</b></p>	<p><b>Routine Handling &amp; Use:</b> Avoid breathing metal fumes or dust generated during machining operations. Practice good housekeeping.</p> <p><b>Non-Routine Handling &amp; Use:</b> Not applicable.</p> <p><b>Storage:</b> Store away from acids and incompatible materials.</p>
<p><b>Spill, Leak and Disposal Procedures</b></p>	<p><b>General Spill or Leak Procedures:</b> All materials should be handled and transported off-site in accordance with federal, state, and local regulations.</p>
<p><b>Regulatory Information</b></p>	<p><b>SARA Section 313 Notification:</b> Contains no listed substances present above the de minimis concentrations listed in 40 CFR 372 (2002). Please contact Western Tube &amp; Conduit for an update prior to completing any EPCRA report.</p> <p><b>VOC Content, Material:</b> 0</p> <p><b>VOC Content, Less Water:</b> 0</p> <p><b>Clean Air Act Ozone Depleter:</b> None listed</p> <p><b>DOT Proper Shipping Name:</b> Not regulated</p> <p><b>DOT Hazard Class:</b> None</p> <p><b>40 CFR 355 Reportable Quantity:</b> None listed</p> <p><b>49 CFR 171 Reportable Quantity:</b> None listed</p> <p><b>California Proposition 65:</b>  <b><u>WARNING: This product contains chemicals known by the State of California to cause cancer, birth defects, or other reproductive harm.</u></b></p>